



## CARPET SPIN DRAINER

### Description

The carpet enters the machine in a rolled state. During the first spin, the carpet unrolls and adapts to the cage's shape. With this system, the carpet is not kinked, and the drying quality achieved is the best currently available on the world market. Then, the spin drainer achieves the maximum speed and spins the carpet within 3 minutes according to the factory settings. You can prolong the spinning process up to 4 minutes by a single push on the button.

When installing the machine no floor foundations are required as the machine is fitted with four elastic devices that absorb vibrations, resulting in low noise (<75 dB). For door opening and closing the air pressure is required. You can achieve it by connecting the machine to 1,5 PS compressor with 25 liters tank.

The spin is equipped with safety device to prevent imbalances. Operated by a single pushbutton. The access door is fitted with a dual safety system. There is a possibility of spinning several small carpets during the same spinning cycle.

### Specifications

Carpets spin drainer	CATINET CE-250-L	CATINET CE-350-L	CATINET CE-450-L
Dimensions L/W/H (m)	3,4 x 0,9 x 1,20	4 x 0,9 x 1,20	5 x 1 x 1,4
Power (kW)	5,5	5,5	7,5
Weight (kg)	805	954	1.180
Max. carpet width (m)	2,5	3,5	4,5
Draining factor G	500	300	150
Spin speed (rpm)	1500	1050	750
Cylinder diameter	44 cm	44 cm	56 cm
Total spin time (min)	3	3	3
Air pressure required (door open)	5 bar	5 bar	5 bar



### Characteristics

- free-standing
- large capacity drain
- automatic controller cycle
- direct position next to the wall
- made in stainless steel AISI 304
- programmable length of spinning cycle

[www.carpetwashing.com](http://www.carpetwashing.com)

Catinet's Central Europe & Balkans Exclusive Distributor